Code No: **20ME3O01**

II B. TECH I SEMESTER REGULAR EXAMINATIONS, MARCH - 2022 THERMODYNAMICS

(MECHANICAL ENGINEERING)

Time: 3 Hours Max. Marks: 70

Note: Answer **ONE** question from each unit (5 × 14 = 70 Marks)

UNIT-I

- 1. a) What do you understand by path function and point function? What are exact [6M] and inexact differentials?
 - b) A mass of 1.5 kg of air is compressed in a quasi-static process from 0.1 MPa [8M] to 0.7 MPa for which pv=constant. The initial density of air is 1.16 kg/m³. Find the work done by the piston to compress the air.

(OR)

- 2. a) Determine the work done by the air which enters into an evacuated vessel [7M] from atmosphere when the valve is opened. The atmospheric pressure is 1.213 bar and 1.5 m³ of air at atmospheric condition enters into the vessel.
 - b) Discuss the concept of Thermodynamic equilibrium.

[7M]

UNIT-II

3. a) Show that energy is a property of a system.

- [6M]
- b) During one cycle the working fluid in an engine engages in two work [8M] interactions: 15kJ to the fluid and 44 kJ from the fluid, and three heat interactions, two of which are known: 75 kJ to the fluid and 40 kJ from the fluid. Evaluates the magnitude and direction of the third heat transfer.

(OR)

- 4. a) Write the steady flow energy equation for a single stream entering and a single [6M] stream leaving a control volume and explain the various terms in it.
 - b) In a steam power station, steam flows steadily through a 0.2 m diameter [8M] pipeline from the boiler to the turbine. At the boiler end, the steam conditions are found to be: p = 4 MPa, t = 400° C, h= 3213.6 kJ/kg, and v = 0.073m³/kg. At the turbine end, the conditions are found to be: p = 3.5 MPa, t = 392°C, h = 3202.6 kJ/kg, and v = 0.084 m³/kg. There is a heat loss of 8.5 kJ/kg from the pipeline. Calculate the steam flow rate.

UNIT-III

5. a) What is a PMM2? Why is it impossible?

[6M]

b) A cyclic heat engine operates between a source temperature of 800°C and a [8M] sink temperature of 30°C. What is the least rate of heat rejection per kW net output of the engine?

(OR)

6. a) State and prove Clausius theorem.

- [6M]
- b) A reversible heat engine operates between two reservoirs at temperatures of [8M] 600°C and 40°C. The engine drives a reversible refrigerator which operates between reservoirs at temperatures of 40°C and 20°C. The heat transfer to the heat engine is 2000 kJ and the net work output of the combined engine refrigerator plant is 360 kJ.
 - (a) Evaluate the heat transfer to the refrigerant and the net heat transfer to the reservoir at 40° C.
 - (b) Reconsider (a) given that the efficiency of the heat engine and the COP of the refrigerator are each 40% of their maximum possible values.

UNIT-IV

- 7. a) Draw the phase equilibrium diagram for a pure substance on h-s plot with [7M] relevant constant property lines.
 - b) Ten kg of water at 45°C is heated at a constant pressure of 10 bar until it [7M] becomes superheated vapour at 300°C. Find the change in volume, enthalpy, internal energy and entropy.

(OR)

- 8. a) Explain specific Heats, Internal Energy, and Enthalpy of an Ideal Gas and [7M] show the relation between them.
 - b) Express the changes in internal energy and enthalpy of an ideal gas in a [7M] reversible adiabatic process in terms of the pressure ratio.

UNIT-V

9. a) Write a short note on

[6M]

- (i) Mass and Mole fraction (ii) Dalton's law of partial pressure
- (iii) Amagats' law of additive volumes.
- b) A vessel of 0.35 m³ capacity contains 0.4 kg of carbon monoxide (molecular [8M] weight = 28) and 1 kg of air at 20^oC. Calculate: (i) The partial pressure of each constituent, (ii) The total pressure in the vessel, and The gravimetric analysis of air may be taken as 23.3% oxygen (molecular weight = 32) and 76.7% nitrogen (molecular weight = 28).

(OR)

10. a) Explain about adiabatic saturation temperature.

[7M]

b) Explain with a neat sketch the constant property lines in a psychrometric chart. [7M]

* * * * *